

TurnPro™

HYDRAULIC SWAGING TOOL

The TurnPro Hydraulic Swaging Tool swages 3/4" inch and larger SSP Duolok tube fitting ferrules onto the tubing prior to assembly to the fitting body. Using hydraulic pressure, the SSP Hydraulic Swaging Tool overcomes the challenge of manually applying the torque required to install 3/4" inch and larger tube fittings. The SSP Hydraulic Swaging Tool reduces installation time and assures sufficient make-up for leak-tight connections on larger Duolok tube fitting sizes.



Part Number	Description	List Price	
TP-ITSD1632HST	Swage Tool Assembly	\$6,500.00	
TP-ITSD32HSTP	Swage Tool Piston 2"	\$500.00	
TP-ITSD2024HSTA	Swage Tool Adapter 1-1/4" - 1-1/2"	\$500.00	
TP-ITSD24HSTP	Swage Tool Piston 1-1/2"	\$500.00	
TP-ITSD20HSTP	Swage Tool Piston 1-1/4"	\$500.00	
TP-ITSD16HSTA	Swage Tool Adapter 1"	\$500.00	
TP-ITSD16HSTP	Swage Tool Piston 1"	\$500.00	
TP-ITSD12HSTA	Swage Tool Adapter 3/4"	\$500.00	Available Spring 2013
TP-ITSD12HSTP	Swage Tool Piston 3/4"	\$500.00	Available Spring 2013

KEY BENEFITS

- ▶ Places no initial strain on nut, fitting body threads or fitting body sealing surfaces.
- ▶ Preswages SSP Duolok tube fitting ferrules onto tubing.
- ▶ Installed fittings are 100% gaugeable.

KEY FEATURES

- ▶ Quick and easy tooling changes to install 3/4", 1", 1-1/4", 1-1/2" and 2" Duolok tube fittings.
- ▶ Instructions printed on tool base.
- ▶ Rugged plastic, wheeled case with pull handle.
- ▶ View window for verification of complete swage.
- ▶ Minimal setup time.

SSP · 8250 BOYLE PARKWAY · TWINSBURG, OH 44087 · +1.330.425.4250

100% Made in the U.S.A.

mySSPusa.com/TurnPro

